

FS2000AC Wireless Bridge



Features

The FS2000AC Wireless Bridge Kit is a ruggedised, high performance wireless bridge system. It is capable of delivering over 600Mbit-sec of usable data throughput and is specifically designed to target longer range applications between 3 and 10km.

The FS2000AC is built upon FreeSpace Networks' Scorpion platform and integrates a high gain, 22dBi MIMO antenna. The FS2000AC provides a radical leap in performance when compared to existing legacy solutions and can deliver up to 6 times the data throughput.

The FS2000AC supports all 5GHz license exempt frequencies and has been optimised for point to point wireless applications including high bandwidth building links for data and voice, leased fibre replacement and longer range wireless CCTV applications.

In addition to supporting standard 802.11ac operation, the FS2000AC also offers the ability to interface with legacy equipment, including the FS1000/FS2000. With its built in 128-bit AES-CCM hardware encryption, secure management interface and MAC address access control, the FS2000AC provides a superior level of transmission protection and data security.

Product Highlights

- 600+ Mbit/sec peak throughput
- Ideal for medium and long distance applications
- 4.9- 6.1 GHz operation, subject to local restrictions
- 22dBi 12° dual polarised 2x2 integrated antenna
- Factory configured bridge kit
- Rugged IP67 enclosure
- Up to 26dBm transmit power
- Full Duplex 10/100/1000 Gigabit Ethernet
- DFS/TPC support to EN301893 v1.5.1 (DFS3.0)
- Dynamic transmit optimisation
- 15W under full load

Applications

The FS2000AC is an ideal choice for longer range applications that cannot be satisfied by the FS1000N wireless bridge.

Applications include :

- Wireless transmission of
 - CCTV
 - DATA
 - VOIP
- Leased fibre replacement
- Rural broadband Internet access
- High capacity trunk links & back-haul
- Citywide networks
- Long range wireless CCTV transmission
- Temporary networks for:
 - Public Events
 - Construction Projects
 - Marine Applications



Abicom International T/A
FreeSpace Networks

The Innovation Centre
Warwick Technology Park
Gallows Hill
Warwick
CV34 6UW
01926623309

FS2000AC Wireless Bridge

Hardware Specifications

RADIO	
Operating frequency	5.1 - 5.875GHz (depending on local legislation)
Modulation	OFDM: 16QAM, 256QAM (802.11ac) with automatic rate adaptation
Maximum RF output power	26dBm (400mW), HT40 2x2 MCS15 Mode
Antenna	22dBi 12° dual polarised 2x2 integrated antenna
Maximum EIRP	40dBi (Automatic adjustment based upon territory setting)
Maximum datarate	866 Mbps
DFS/TPC support	conforms to 802.11h
Security	128bit AES-CCM Hardware Cipher
Interface	
Ethernet	802.3ab, 802.3u, 802.3i (10/100/1000 Mbit Ethernet) with auto cross-over and negotiation
Ethernet connector	standard RJ45 with field installable IP67 fitting
Power	
PSU type	802.3af (48Vdc) Power Over Ethernet (PoE+)
Typical power consumption	15W
Environmental	
Environment	IP67
Operatng temperature	-20 to +60°C
Humidity	95% RH Non-condensing
Physical	
Dimensions	320mm x 320mm x 80mm
Weight	3kg
Approval	
IR2006 (5150-5725MHz) IR2007(5725-5850MHz), EN302-502(DFS/TPC), EN301-489 (ERM/EMC) EN60950 (Safety)	
Warranty	
1 Year return to base	

Software Specifications

Management Interface	
Remote access	WifiMonitor NMS Tool, Onboard Webserver
Remote Monitoring	SNMP, WiFiMonitor
Security	
Encryption	128bit AES-CCM with WPA/WPA2 Support
Device Access Control	MAC based Access/Deny Control
Data management	
VLAN	802.1q and trunked applications
QoS	802.1p